

Slender, beautiful, tremendous sound: FS 57



improved stability

The slender 2 way floorstander of the new entry class series establishes a new record in terms of value for money. The FS 57 provides strong bass, high efficiency, elegant design and smart features.

Technical features

- 2 x 145 mm high-power woofer for balanced sound, deep bass and high efficiency, with cellulose diaphragm, concave-shaped dome and capton bobbin for good power handling
- 1 x 25 mm tweeter with neodymium magnet system and star-shaped cooling attachment on the terminal
- gold-plated mono binding posts with transparent screw-type terminal
- MDF cabinet with internal tension rods and robust base
- the bass port's double flare design minimises air noise and friction losses
- overload-protection provides trouble free operation: this loudspeaker is recommended for use with 20-100W/ch powerful amplifiers
- elegant design: all driver baskets and mounting plates of the 50 series are in the new colour *titan metallic*, specially designed for ELAC
- robust base with spikes for decoupling and for

Finishes: graphite maple, cherry, silver



Specifications	ELAC FS 57	Crossover Frequency	3000 Hz
Dimensions H x W x D	925x 220x265 mm	Nominal / Peak Power Handling	80 W / 120 W
Weight	14 kg	Frequency Range	42-23000 Hz
Type	2 way, bass reflex	Sensitivity	90 dB/2.8V/m
Woofer	2 x 145 mm cone	Minimum Impedance	3.4 ohms at 250 Hz
Tweeter	1 x 25 mm dome	Nominal Impedance	4 ohms
Recom. Amplifier Power at Nominal Impedance	20 – 150 W/channel		

Product Information

FINEST GERMAN ENGINEERING
ELAC